

PRODUCT DATA

Low Vis Gear Lube 75W-90

High Performance Manual Gearbox Lube

Description

Gulf Western Low Vis Gear Lube 75W-90 is a high performance gear oil for modern manual transmissions.

Low Vis Gear Lube 75W-90 is also recommended when SAE 75W or 80W are specified.

It has the balance of viscosity and frictional properties, which ensure good shift feel and fast gear changes. This oil is ideal for modern 4 and 5 speed manual gearboxes which need low viscosity oil for cold changing yet still need an SAE 90 when warm, to ensure quiet running.

Summary of Benefits

- Low Vis Gear Lube 75W-90 has a shear stable formulation, which exceeds the stringent 75W-90 requirements, ensuring full protection during extended drain intervals.
- Naturally high viscosity index, stops cold shift baulking, yet still provides quiet running at operating temperature.
- Reduces friction hence lowering operating temperature and frictional power losses.

Specifications

Low Vis Gear Lube 75W-90 meets the performance requirements of:

- SAE Viscosity 75W-90
- API GL4 / GL5
- Borg Warner 5M-42
- Ford ESP-M2C83-C
- Mitsubishi ES-X-64021

Low Vis Gear Lube 75W-90

High Performance Manual Gearbox Lube

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

Typical Characteristics

Grade:	Low Vis Gear Lube		75W-90
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.8871
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	151
@ 100°C	ASTM D445	cSt	18
Viscosity Index	ASTM D2270	-	140
Apparent Viscosity	ASTM D2983	сР	150,000
(Brookfield @ -40°C)			max
Pour Point	ASTM D97	°C	-30
Flash Point (COC)	ASTM D92	°C	>250

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

Pack Sizes Available:

205lt - 30050, 60lt - 36050, 20lt - 32050, 5lt - 30550, 1lt - 30150







Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au Web: www.gulfwestern.com.au