



**GULF WESTERN**

THE TOUGH AUSTRALIAN

PRODUCT DATA

# Superdraulic<sup>®</sup> 22, 32, 46, 68, 100, 150, 220

High Performance Anti Wear Hydraulic Oil

## Description

Superdraulic<sup>®</sup> is a range of high performance anti wear hydraulic oils. They have been formulated using highly refined base oils fortified with zinc anti wear, oxidation corrosion inhibitors and anti foam additives.

This produces a highly thermally stable fluid capable of handling high loads and high temperatures. The Superdraulic<sup>®</sup> range is available in ISO grades 22, 32, 46, 68, 100, 150 and 220.

## Compatibility

Superdraulic<sup>®</sup> is compatible with most pumps, valves, and seal materials. However, like all hydraulic oils containing zinc anti wear additives, it is not suitable for use with pumps having silver plated parts (e.g. some Lucas units).

# Superdraulic® 22, 32, 46, 68, 100, 150, 220

High Performance Anti Wear Hydraulic Oil

## Summary of Benefits

- Improved equipment life and decreased downtime due to superior wear and corrosion protection.
- Enhanced chemical and thermal stability provide long fluid life and permit higher operating temperatures.
- Excellent air release and anti-foam properties to prevent cavitation and oxidation.
- Excellent filterability even when contaminated, thereby preventing filter blockages. This saves filter replacement costs and down time.
- Enhanced low frictional characteristics to prevent the occurrence of "stick slip."

## Specifications

Superdraulic® meets the following international performance specifications:

- ISO Viscosity Grades 22, 32, 46, 68, 100, 150, 220
- Cincinnati Milacron P68, P69, P70
- Denison HF-0, HF-1, HF-2
- DIN 51 524 Part 2 (HLP type oils)
- US Steel 136, 127
- Vickers 1-286-S, M2952-S

Superdraulic® meets the requirements of the following pump manufacturers:

- |             |                         |
|-------------|-------------------------|
| • Hagglund  | • Rexroth               |
| • Danfoss   | • Linde                 |
| • Bosch     | • Commercial Hydraulics |
| • Racine    | • Vickers               |
| • Sunstrand | • Denison               |
| • Oilgear   | • Cincinnati Milacron   |

## Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

## Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

# Superdraulic® 22, 32, 46, 68, 100, 150, 220

High Performance Anti Wear Hydraulic Oil

## Typical Characteristics

Grade:	Superdraulic®		22	32	46	68	100	150	220
	Test Method	Units							
Density @ 15°C	ASTM D1298	kg/L	0.8650	0.8682	0.8773	0.8819	0.8883	0.8901	0.8939
Kinematic Viscosity									
@ 40°C	ASTM D445	cSt	22	32	46	68	100	150	220
@ 100°C	ASTM D445	cSt	4.3	5.4	7	9	11.0	14.5	18.7
Viscosity Index	ASTM D2270	-	101	102	109	107	94	95	95
Pour Point	ASTM D97	°C	-27	-27	-27	-27	-27	-27	-27
Flash Point (COC)	ASTM D92	°C	>224	>224	>224	>224	>224	>224	>224
FZG Gear Test (A/8.3/90°C)	IP 334	Stage Failure	11	11	11	11	11	11	11
Colour	ASTM D1500	-	1.5	1.5	1.5	1.5	1.5	1.5	1.5

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

### Pack Sizes Available:

- 22: IBC - 30078B, 205lt - 30078, 20lt - 32078
- 32: IBC - 30061B, 205lt - 30061, 20lt - 32061
- 46: IBC - 30062B, 205lt - 30062, 20lt - 32062
- 68: IBC - 30063B, 205lt - 30063, 20lt - 32063
- 100: IBC - 30064B, 205lt - 30064, 20lt - 32064
- 150: 205lt - 30070, 20lt - 32071
- 220: 205lt - 30071, 20lt - 32071



## GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: [sales@gulfwestern.com.au](mailto:sales@gulfwestern.com.au)

Web: [www.gulfwestern.com.au](http://www.gulfwestern.com.au)

ACN 087 558 398