



GULF WESTERN

THE TOUGH AUSTRALIAN

PRODUCT DATA

ATF Dex III

Automatic Transmission Fluid

Description

ATF Dex III is a transmission fluid designed for use in automatic transmissions where Dexron[®] III, Dexron[®] II or Mercon[®] fluids have been specified. It is also commonly used as a power steering fluid.

It is suitable for use with new technology transmission components and meets the need for improved fluid stability and reliability under increased operating temperature. ATF Dex III meets the most demanding of all ATF specifications.

Summary of Benefits

- Approved for a wide range of automatic and hydraulic transmissions.
- Cost effective option to Dexron[®] III products.
- May be used for service fill or top up where Dexron[®] II, Dexron[®] III and Mercon[®] fluids are specified.
- Provides excellent protection of mobile hydraulic pumps such as those of Denison, Sperry Vickers and Sundstrand.
- Greatly improved low temperature properties for smooth cold shifts.
- Excellent shear stability for long fluid and component life.
- Has unsurpassed retention of frictional coefficient, for consistently smooth gear changes.

Specifications

ATF Dex III meets the following international performance specifications:

- General Motors
Dexron[®] III (F30556)
- Caterpillar TO-2
- Allison C4
- Ford Mercon[®]

ATF Dex III

Automatic Transmission Fluid

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

Typical Characteristics

Grade:	ATF Dexron III	Dex III	
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.8612
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	42
@ 100°C	ASTM D445	cSt	8.1
Viscosity Index	ASTM D2270	-	170
Pour Point	ASTM D97	°C	-42
Flash Point (COC)	ASTM D92	°C	193
Appearance			Red

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

Pack Sizes Available:

IBC - 30041B, 205lt - 30041, 60lt - 36041, 20lt - 32041, 5lt - 30541, 1lt - 30141



GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398