



# GULF WESTERN

THE TOUGH AUSTRALIAN

## PRODUCT DATA

# Agritrans

## Universal Tractor Transmission Oil

### Description

Agritrans is a multi purpose oil suited to tractors requiring a common oil for transmissions, hydraulics, differentials, final drives, wet clutches and brakes. The anti squawk additive ensures effective operation of wet brakes.

Agritrans has been specifically developed to meet a wide range of specifications from most modern tractor and hydraulic pump OEM's.

Gulf Westerns additive technology has been field tested in over 250 tractors and that combines to more than 200,000 hours of field tests.

### Summary of Benefits

Agritrans offers:

- Superior gear wear protection.
- Correct frictional characteristics ensure quiet wet brake operation.
- Proven Field performance.
- Good anti foam characteristics.
- Excellent shear stability and thermal/oxidation stability provide long fluid life.
- Good water tolerance ensures hydraulic performance is maintained.
- Low Copper activity.
- Good filterability.
- Excellent anti squawk properties.

# Agritrans

Universal Tractor Transmission Oil

## Specifications

Hydraulic Pump Performance	Sperry Vickers I-286-S (industrial), M-2950-S (mobile) Denison HF-0, HF-1, HF-2 Sundstrand Hydraulics Cincinnati Milacron P-68, P-69, P-70
John Deere	JDM J20c, J14A, J20D (factory Fill) JDM J20A, B. JDM J14B, C. JDM J21A, JDT303, Quatrol®
New Holland Ford (New Holland Group)	ESN-M2C134-D (FNHA-2-C-201.00) FNHA-2-C-200A FNHA-2-C-200.00* (Super All Season Driveline and hydraulic fluid FNHA-2-C-201 – F200-a”) (* Winter grade) M2C134-A, B, C, D M2C43, M2C41-B, M2C92-A M2C48A, B M2C53A, B NB 410B MAT 3525, 3526 35VQ25 and M-2952-S
Massey Ferguson	M-1141 (EP trans fluid), M-1143 M-1135 (Trans / hydraulic - Europe) M-1145 (Trans / hydraulic - Europe) M-1127 A and M-1127B M-1110 M-1129A
Case Corp (JI Case and International Harvester)	JIC-145, JIC-143, JIC-144, JIC-185 MS – 1210 MS – 1204 MS – 1205 MS – 1206 MS – 1207 B5 and B6 White Farm Q1826, Q-1705, Q-1766, Q-1802 AGCO, Powerfluid 821XL Steiger SEMS 17001 Versatile Deutz-Allis Fiat-Hesston NB 410B MAT 3525

# Agritrans

Universal Tractor Transmission Oil

## Specifications (continued)

Kubota	UDT Hydraulic Fluid (UTF)
White Farm (Oliver)	Q – 1826 Hydraulic transmission fluid (HTF) Q1766, Q1722, Q1766B, Q1705, Q1802, TYPE 55
AGCO / Duetz-Allis / Allis- Chalmers	Power Fluid 821 XL , 272843, 257541, 246634
Landini	Tractor II Hyd
Allison	C2, C3, C4
Caterpillar	TO-2
Sperry Vickers	M-2950-S, I-286-S Ind
Clarke	TA-12, TA-18, HR500, HR600
API	GL-4
ZF	TEML 03E/ TEML 03F // TEML 05E/ TEML 05F / TEML 06K
Komatsu Dresser	B-06-0001 and B-06-0002
Renk Doromat	873, 874 A and 874 B (current)
Versatile	Specification 23M or 24M (Versatile)
Hesston-Fiat (tractors only)	AF-87, Multi-F, Multi-G (Current)
Volvo CE	WB-101

## Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

## Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

# Agritrans

Universal Tractor Transmission Oil

## Recommended for use in the following OEM Agricultural Equipment (7)

Denison HF-0, HF-1 & HF-2 (current) (6)

DEXRON and Type A, Suffix A (tractor)

Eaton Hydraulics

Ebru

Fendt

Ford ESN-M2C86-B and ESN-M2C86-C (5)

Fort and Pegoraro (part of Argo S.p.A.)

Gleaner (part of AGCO)

Hurlimann

Ingersoll Rand

IMT

International Harvester

International Hough (Dresser)

JCB

JI Case

KH Duetz

Kioto

Komatsu and Komatsu/ Dresser

Kubota

Rockwell Transmissions

Same Deutz-Fahr

Sauer Sundstrand

Schluter

Steiger

Steyr Daimler

Sundstrand Hydraulics (Plessey)

Taylor

Universal

Ursus

Valmet

Valpadana (part of Argo S.p.A.)

Valtractores

Versatile

Vickers Hydraulics

Volvo

Yanmar

Zetor

# Agritrans

Universal Tractor Transmission Oil

## Typical Characteristics

Grade:	Agritrans	10W-20	
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.8892
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	70
@ 100°C	ASTM D445	cSt	8.9 (9.5max)
Viscosity Index	ASTM D2270	-	110
Pour Point	ASTM D97	°C	-35
Flash Point (COC)	ASTM D92	°C	190

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

### Pack Sizes Available:

IBC - 30044B, 205lt - 30044, 60lt - 36044, 20lt - 32044



## GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: [sales@gulfwestern.com.au](mailto:sales@gulfwestern.com.au)

Web: [www.gulfwestern.com.au](http://www.gulfwestern.com.au)

ACN 087 558 398