



GULF WESTERN

THE TOUGH AUSTRALIAN

PRODUCT DATA

Ultra Clear Gear Oil Diff Lube LS 80w140

Fully Synthetic Water Clear Limited Slip Diff Lube

Description

Gulf Western Ultra Clear Gear Oil Limited Slip is a fully synthetic ultra clear gear lubricant for differentials with or without 'limited slip'. The Ultra Clear Gear Oil range is blended from fully synthetic base stock, offering superior performance to that which can be offered by a mineral gear oil.

These lubricants are extreme pressure heavy duty gear oils recommended for hypoid or spiral bevel axles, gears and steering boxes in automotive and heavy transport equipment.

Gulf Western Ultra Clear Gear Oil Limited Slip is available in SAE viscosity grade 80w140.

Summary of Benefits

- Gulf Western Ultra Clear Diff lube synthetic formulation is more resistant to oil oxidation, giving longer drain intervals.
- Excellent resistance heat degradation allows this grade to operate at higher temperatures than a mineral gear oil.
- Naturally high viscosity index, reduces wear at start up yet still provides better protection at operating temperature.
- Reduces friction hence lowering operating temperature and frictional power losses.

Specifications

Ultra Clear Diff Lube meets the performance requirements of:

- SAE Viscosity 80W-140
- MIL -L-2105D
- API GL4 and GL5
- Mack GO-J

Ultra Clear Gear Oil Diff Lube LS 80w140

Fully Synthetic Water Clear Limited Slip Diff Lube

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

Typical Characteristics

Grade:	Ultra Clear Diff Lube	80W-140	
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.867
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	300
@ 100°C	ASTM D445	cSt	30.0
Viscosity Index	ASTM D2270	-	155
Pour Point	ASTM D97	°C	<-30
Flash Point (COC)	ASTM D92	°C	235
Colour	ASTM D1500	-	1.5

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

Pack Sizes Available:

IBC - 30055B, 205lt - 30055, 20lt - 32055, 4lt - 30455



GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398